

Pro-Flex 120B Contour Rough / Finishing Mower Field Proven: Quality, Dependability, and Value

The **Pro-Flex 120B** is the most widely used pull-behind contour finishing mower. It has become the 'go-to' contour and rough mower due to its reliability, a 10' wide cut, and its versatility. With 5 independent floating decks, the **Pro-Flex 120B** will easily follow contour changes that are found on golf courses and campuses, producing a uniform quality cut that is demanded by Superintendents and members alike.

Unlike a self-contained, ride-on rough mower, the **Pro-Flex 120B** provides increased equipment utilization as the tractor can be used for other tasks. This means a lower total cost of ownership. Additionally, the required horsepower for the utility tractor connected to a **Pro-Flex 120B** is about half of what a Tier 4 self-contained mower requires. This directly translates to a large saving in fuel cost, year after year!

The **Pro-Flex 120B** has several standard features that are important on a pull-behind contour mower, but are only available from Progressive! Features such as: a shock absorber on each independent, floating deck to minimize deck bounce; a unique 4-way rotating clevis that allows the tractor and mower to traverse uneven terrain without affecting one another; and a conventional style drawbar design that makes turning and reversing feel very familiar to an operator. Utilizing the tractor for other tasks is a key advantage so we made connecting a **Pro-Flex 120B** to the tractor easy, thanks to an adjustable clevis, a low tongue weight, and an auto-lock PTO shaft.

Your choice! The **Pro-Flex 120B** is available in either traditional RED or for a 'packaged look' it is also available with industry GREEN paint.

Originally introduced in 1999, the **Pro-Flex 120B** is well known as a durable, reliable rotary finishing mower that is now easier to maintain than ever before. The **Pro-Flex 120B** is "**The Better Built Choice**".

The Better Built Choice.™

Superintendent Series



The **Pro-Flex 120B** has five individual mowing decks that produce a superior cut while conforming to contour changes. Each deck floats independently up and down, fore and aft, as well as side to side of the adjacent deck, for superior cut quality. Each deck is equipped with two anti-scalp rollers for peace of mind.

Ideal for making a stepped or a transition first-cut:

As cut height is easily set on each deck of the **Pro-Flex 120B**, Superintendents have the option of setting the **Pro-Flex 120B** to make a stepped or a transition first-cut along the outer edge of the fairway. This provides an easy way to help speed play, something competing contour mowers cannot do!

Pro Lift-N-Turn™

An industry exclusive feature - not found on other contour mowers! **Pro Lift-N-Turn™** allows the decks to be raised slightly off the ground with the PTO still engaged. Crossing a cart path or other minor obstacles has never been easier. When initially engaging the PTO, the operator can lift the decks so the blades are above the uncut grass, reducing stress on the complete drivetrain.

Smart by design:


The standard equipment <u>automatic wing lock valve</u> simplifies operation and makes operating the **Pro-Flex 120B** easier than ever before! For an even cut, a 4-way rotating clevis allows the tractor and mower to traverse uneven terrain without one affecting the other. A full transport frame provides the ability to mow in a controlled manner even while backing up. A mulching kit is available making the **Pro-Flex 120B** ideal for fall leaf clean-up.

Rubber Damped, Automatic Belt Tensioners

A simple belt drive system transfers power from the input PTO to the 5 floating mower decks. Belt tension for each belt is maintained by a rubber damped tensioner that maintains the correct belt tension. This extends belt life and ensures a positive drive as the **PF 120B** flexes over changing ground contours.

Easy Routine Maintenance:

Daily greasing is eliminated, thanks to the <u>automatic belt tensioners</u>, the <u>maintenance free blade spindles</u> and the <u>100 hour PTO shaft greasing intervals</u> that are standard equipment! Combining this with a reduction in grease points provides an additional measure of comfort – gone is the fear that a missed service point by un-familiar maintenance personnel will render the mower out of service and put grounds maintenance behind schedule.









30 to 40

8.5 feet

4.1 feet

11 feet

2.075 lb.

1 to 31/4 inches

Pro-Flex 120B Contour / Rough Finishing Mower Specifications

Recommended PTO H.P.:

Cut Height Range:

Transport Width:

Transport Height:

Transport Length:

Operating Weight:

Part Number: 601205B (Traditional Red)

602711B (Industry Green)

Cutting Width: 10 feet

Mowing Capacity: 4 mph 4.4 acres per hour*

6 mph 6.5 acres per hour*

Turning Radius: 16" uncut circle **Transport Tires**: 18.5 x 8.5 - 8 4ply

*Assumes no overlap or turning

