

The Toro logo, featuring the word "TORO" in white, bold, sans-serif capital letters inside a red rounded rectangle.

Versa Vac[®]

SWEeper/VACUUM

F E A T U R E S

- 6.5 cu. yd. (5 cu. m) capacity
- Two quick-change deck options
- Self-contained hydraulic controls

One versatile vacuum.

The Versa-Vac, the largest Toro turf sweeper, has an impressive 6.5 cu. yd. (5 cu. m) capacity. Factor in the leaf-shredding action of the impeller fan and you'll hardly ever have to stop to unload. The cargo door and dump operate hydraulically with controls that sit directly behind the tractor seat for easy access. The hydraulics, sweeping decks and impeller fan are all powered by a 540 PTO drive with enough muscle to sweep up any debris.

toro.com





Versa-Vac™

The Toro® Versa-Vac tackles debris management challenges to meet your collection needs.



VERSA-VAC, MODEL 07053*	
POWER SUPPLY	Power source: 35 PTO hp and larger turf tractor with 540 PTO output shaft, double CV drive line, drive ratio to Impeller: .486 : 1, drive ratio to pump input shaft from impeller shaft: .389 : 1.
FAN IMPELLER	32" (81.3 cm) diameter impeller, 8 blades reinforced .25" (6.4 mm) steel, 9.375" (23.8 cm) wide (radial design) welded to a 27" (68.3 cm) diameter base plate.
DRIVE	Belt drive from input shaft to impeller shaft (4-5VX), belt drive from impeller shaft to pump input shaft (2-5VX).
MAIN FRAME	One piece welded frame of .25" (6.4 cm), 7 and 10-guage formed steel.
WHEELS AND TIRES	Turf tire, size 24 x 13.00-nhs 4-ply. Stamped and welded steel wheels rated up to 1,800 lbs. (817 kg).
HOPPER	Volume 6.5 cubic yard, self-cleaning tapered box, dump hopper is operated hydraulically by one control, with self opening and closing door, dump hopper hydraulically lifted with a 3 x 18 hydraulic cylinder, vented roof sections with dust hoods to direct dust away from operator.
DIMENSIONS	Width: 78" (198 cm), Height: 83" (211 cm), Length: 15'5" (4.7 m), Weight: 2,300 lbs. (1,044 kg)
OPTION	20' (6.1 m) handheld hose.
WARRANTY	Two-year limited.
COMBINATION DECK, MODEL 07082	
FLAIL ROTOR	72 hardened, straight steel flails with adjustable spacing.
FINGER ROTOR	Four rows of 6" (15 cm) long fingers with 22 fingers per row.
OPERATING WIDTH	72" (183 cm)
CASTER WHEELS	4-adjustable pneumatic caster wheels with full width anti-scalp roller, adjustable in .5" (12.7 mm) increments.
WEIGHT	700 lbs. (318 kg)
RUBBER FINGER DECK, MODEL 07081	
ROTOR	Four rows of 6" (15 cm) long fingers with 22 finger per row.
OPERATING WIDTH	72" (183 cm)
CASTER WHEELS	4-adjustable pneumatic caster wheels, adjustable in .5" (12.7 mm) increments.
WEIGHT	280 lbs. (127 kg)

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

