

The Toro logo is displayed in white, bold, sans-serif capital letters inside a red rounded rectangle.

# Multi Pro<sup>®</sup> WM

200-GALLON SPRAYER ACCESSORY  
WORKMAN HD SERIES

## F E A T U R E S

- **Six Diaphragm Pump** – *An Industry Exclusive*  
– this oversized pump satisfies the highest spray rates while simultaneously supplying generous agitation flow
- **200 gal (757 L) Elliptical Chemical Tank** –  
Thoughtfully designed polyethylene tank has no shelves or corners for chemical to stick on, which helps ensure a 99% spray out.
- **Sprayer Control Console** – *InfoCenter™*  
pressure gauge and sprayer control switches are all located in a unique console featuring Toro's exclusive 'Quick Find™' feature which intuitively helps the operator find boom and actuator switches on the console without looking at them.
- **Rugged Triangular Spray Boom** –  
Standard three section, 18.5' (5.6 m) boom width provides fore and aft breakaway on impact while protecting nozzles. Raises into a crisscross position for storage and transportation. Optional 20.5' (6.25 m) boom width extension kit available.

## Precise spray control for a Workman<sup>®</sup> vehicle.

The Multi Pro WM spray system for Toro's Workman<sup>®</sup> HD Series utility vehicles leverages the advanced spray system capability of Toro's Multi Pro line and combines functionality with cutting-edge and intuitive sprayer controls. The result is the most advanced, efficient and accurate 200-gallon bed-mounted sprayer accessory for a utility vehicle on the market. Aggressive agitation, faster response times, consistent and accurate application rates, and intuitive rate set up, makes this the sprayer that has it all.



# Multi Pro® WM – 200-Gallon Sprayer Specifications\*

	SPRAYER SPECIFICATIONS
<b>SOLUTION TANK</b>	High-density, impact-resistant polyethylene with large 16" (41 cm) fill well, tapered bottom and sump with drain.
<b>RATED CAPACITY</b>	200 gallons (757 liters).
<b>SPRAY PUMP</b>	Hardi 364/10.0, 6-diaphragm positive displacement pump w/1" (2.5 cm) input shaft; input speed 0-540 rpm; Flow rate 45 gpm (170.3 lpm) @ 40 psi (540 rpm).
<b>AGITATOR</b>	4, side-mounted jet agitation nozzles for full tank agitation.
<b>CONTROLS</b>	Spray pump control switch, agitator jet switch, rate switch, individual boom On/Off switches, boom actuator switches, indicator lights on pump, agitation and boom switches, throttle lock.

	OPEN BOOMS (STANDARD)
<b>BOOM ASSEMBLY</b>	18.5' (5.6 m) three section, triangular truss style open booms. Optional 20.5' (6.25 m) booms available.
<b>BOOM ACTUATORS</b>	Heavy Duty hydraulic lift actuators with nitro-steel plated shafts; 1-3/4" Bore x 10.06" Stroke.
<b>SPRAY NOZZLES</b>	Eleven nozzles turrets, triple turret mount, quick-disconnect with diaphragm check valves.



	MULTI PRO WM ACCESSORIES
<b>CLEANLOAD™ EDUCTOR KIT</b>	This on-board mixing station allows rapid and safe loading of any chemical without the need to first mix into a slurry. Incorporates a built-in bottle wash nozzle and has an optional suction lance to pull in powdered or liquid products from their container. Stores within the width of the machine.
<b>FRESH WATER RINSE KIT</b>	Simplifies and automates the triple-rinse process, saving hours and hours of clean up time.
<b>ELECTRIC HOSE REEL KIT</b>	150' (45.7 m) of hose for hand or walk spraying applications. Convenient electric powered rewind. Spray gun has an adjustable nozzle from stream to fan.
<b>PRO FOAM™ MARKING KIT</b>	Foam dollops ensure accurate parallel path tracking. Select foam independently or both simultaneously.
<b>ULTRA SONIC BOOM™ KIT</b>	New sonar sensors automatically maintain proper spray height over undulating turf.
<b>COVERED BOOM KIT</b>	Extends 12" (30.5 cm) below the boom to minimize chemical drift in breezy conditions while retaining full boom system functionality.
<b>AIR INDUCTION TURBO TWIN JET NOZZLES</b>	Exclusive to Toro in the 0.8 gpm (3.02 lpm), 1.0 gpm (3.79 lpm) and 1.5 gpm (5.68 lpm) sizes, for exceptional contact coverage.
<b>CONTACT &amp; SYSTEMIC NOZZLES</b>	Select the right nozzle for your application by using the new <b>Toro Nozzle Selector</b> - available via <a href="http://Toro.com">Toro.com</a>

## WARNING

THE WORKMAN® IS AN OFF-HIGHWAY VEHICLE, AND IS NOT DESIGNED, EQUIPPED, OR MANUFACTURED FOR USE ON PUBLIC STREETS, ROADS OR HIGHWAYS.

