











Clear the way with the cleanest and most cost-effective turf vacuum on the market. The TV40 is the preferred model for clearing pine needles, grass clippings, debris and animal droppings from artificial turf and city parks. Available in PTO or engine driven units, you'll reduce your turf footprint with the TV40's one-pass performance.

TURF TOW BEHIND MODELS

Turf management solutions with a unique recirculating air system that minimizes dust for a clean sweeping environment.









into narrow spaces.



The trip-and-latch system comfortably opens the hopper door for easy disposal.



Extend your reach with the 12.5 ft. hose for debris clean up in hard to reach areas. (optional)



Freedom to start, control and unload the hopper at your fingertips.



Designed for large area debris removal, the TV60 is the perfect solution to thoroughly

remove grass, leaves, trash and thatch. Improve efficiencies with the 60" wide brush head

for continuous and even coverage pass after pass. Up your game and turn a two-man job

RE & RHD | Powerful pick up performance

into a one-man job using the TV60 RHD's verti-cut and vac technology.

Remove thatch, sweep and vac in one pass with the solid steel 60" verti-cut rotor. (HD model only)



The TV60 can be pulled by a 40HP tractor or a large utility vehicle.



TOW BEHIND MODELS

TV40 RE & RH | TURBO VAC

(TV40~RE) 20 HP Kohler TM gas engine $(TV40~RH)$ None (PTO powered) 20 HP Required
(TV40 RE) Belt driven from engine (TV40 RH) Tractor PTO driven
(TV40 RE) Double v-belt drive with electric clutch (TV40 RH) Hydraulic motor powered by PTO pump
25" dia. abrasion resistant steel with replaceable UHMW poly liner and 1.5" shaft with self-aligned bearings supporting both ends
Access plate for inspection and easy liner replacement
Hydraulic motor-direct drive
Crown AW46; ISO 46 Hydraulic Oil
11 gauge welded and reinforced steel tubing
Greasable bearings and sealed bearings
4 cubic yards
4-bolt wheels and (2) 18.5 x 9.5 tires
(TV40 RE) Engine, blower and brush controls on machine (TV40 RH) Tractor PTO Controls
13.5" dia. x 52" with adjustable gauge wheels
Mechanical trip-and-latch system from operator's seat
Adjustable tongue doubles as pick up height controller
Durable 2-part polyurethane
Minimal dust generated, quiet operation - 90dB, 96db RH
135"L x 64"W x 82"H
(TV40 RE) 1,600 lbs. (726 kg) (TV40 RH) 1,820 lbs. (826 kg)
Brush rotor, rubber finger rotor, curb brush and 8" x 16' remote hose attachment

TUCO DE O DUD I TUDDO VAC

	TV60 RE & RHD TURBO VAC
Engine	(TV60 RE) 23.5 HP EFI engine (TV60 RHD) None (PT0 powered) 40 HP Required
Hydraulics	(TV60 RE) Belt driven from engine (TV60 RHD) Tractor PTO driven
Blower Drive	(TV60 RE) Dual power-band belt driven with electric clutch (TV60 RHD) Hydraulic motor powered by gear pump
Blower Fan	25" dia. abrasion resistant steel with replaceable UHMW poly liner and 1.5" shaft with self-aligned bearings supporting both ends
Blower Discharge	Easy access to blower for liner inspection and replacement
Deck Drive	(TV60 RE) Hydraulic motor-direct drive (TV60 RHD) Hydraulic motor-chain drive
Hydraulic Oil	Crown AW46; ISO 46 Hydraulic Oil
Construction	11 gauge welded and reinforced steel tubing
Bearings	Greasable bearings and sealed bearings
Hopper Capacity	7 cubic yards
Wheels/Tires	6-bolt wheels and (2) 26 x 12 turf tires
Controls	Wireless remote control from operator seat
Rotors	(TV60 RE) 17" dia. x 60" with adjustable skids (TV60 RHD) 12" dia. x 60" with adjustable gauge wheels
Discharge	Hydraulic dump with hydraulic power latches
Tongue & Hitch	Adjustable height tongue with ball hitch
Paint	Durable 2-part polyurethane
Safety Features	Cylinder safety latches, minimal dust generated and quiet operation $(TV60~RE)$ + engine automatically returns to idle while dumping
Dimensions	164"L x 85"W x 85"H
Weight	(TV60 RE) 2,300 lbs. (1,043 kg) (TV60 RHD) 2,250 lbs. (1,021 kg)
Options	Brush rotor, rubber finger rotor and curb brush (TV60 RHD) + verti-cut w/ rubber finger, verti-cut w/ carbide tip

