

TORO®

T5 RAPIDSET® SERIES ROTORS



The Toro® T5 RapidSet rotor can be set in seconds. Engineered to use the slip clutch to adjust the arc, the T5 RapidSet rotor requires NO TOOLS for arc adjustments. Along with a five inch pop-up height of the Lawn model, the T5 RapidSet rotors feature exclusive Airfoil Technology™ standard and low angle nozzles that deliver class-leading distribution uniformity. Designed to save water, save time, and save money, the T5 RapidSet rotor is the only $\frac{3}{4}$ " rotor needed to get the job done.

FEATURES & BENEFITS

RapidSet® Arc Adjustment

Arc adjustments from 40° to 360° can be made quickly with a few twists of the turret – no tools required. The RapidSet slip clutch also protects against gear damage caused by intentional vandalism or inexperienced users.



RapidSet® arc adjustment requires NO TOOLS!

Lawn Model with a 5" Pop-up Height

Fits in the same footprint as many competing 4" rotors for hassle-free retrofits, but delivers an extra inch of pop-up height, allowing the nozzle to clear tall grasses.

Airfoil Technology™ Nozzles

The T5 RapidSet rotor comes with a full set of 8 standard nozzles (25° trajectory) and 4 low angle (10° trajectory) nozzles that utilize proprietary Airfoil Technology, which creates a zone of low pressure just below the main stream to gently guide water downward for unmatched uniformity without forcefully washing out newly-laid seeds.

Design Flexibility

T5 RapidSet rotors are available in Effluent, Shrub, 12" High Pop, and Stainless Steel models.



Effluent
Options
Available



Check
Valve
Options
Available





<i>Base Model</i>	<i>Body</i>	<i>Optional</i>	<i>Optional</i>	<i>Custom Nozzles</i>	<i>Optional</i>	
T5	XX	XX	XX	X.X	E	-RS
T5— T5 RapidSet Series Rotor	P - Lawn S - Shrub HP - High Pop	CK— Check Valve	SS— Stainless Steel riser	1.5-1.5 gpm 2.0-2.0 gpm 2.5-2.5 gpm	E— Effluent	RS— RapidSet
Example: A T5 RapidSet Lawn Pop-up sprinkler with a 2.5 gpm nozzle and Check Valve would be specified as: T5PCK2.5-RS						